

The one that creates a new trend

AnyShop

어느 매장과도 잘 어울리는 디자인,
설계구조를 가진 Trend Item!



다양한 설치 지원
스탠드형, 벽걸이형
월마운트, 키오스크 거치대



카메라(옵션)
매장 보안유지
화상통화



고객용 디스플레이
VFD 타입
2줄 20자



2nd LCD 디스플레이
12.1" 듀얼모니터
해상도 : 1024 x 768



다기능 일체형 장치
마그네틱 카드 리더
스마트 카드 리더



어떤 매장에서든 잘 어울리는 구조

- 외식업, 유통업
- 병원 및 엔터테인먼트 매장
- 스탠드형, 키오스크 거치대 장착으로 공공시설 터치시스템
- 벽걸이용 안내시스템

손쉬운 유지보수/옵션장착

- 착탈식 HDD교체 (드라이버 없이 HDD교체)
- 간편한 힌지와 본체 분리
- 스크류 고정없이 장착할 수 있는 CDP
- 쉬운 듀얼모니터 장착

강력한 쿨링시스템 채택

다양한 칼라 선택 화이트/와인/블랙/기타

다양한 스펙지원

- 저전력, 저발열 Intel Atom CPU
- 속도, 안정성에 뛰어난 Mobile CPU
- 최상의 속도를 자랑하는 Dual Core CPU

System



	AnyShop M	AnyShop P	AnyShop D5
CPU	Intel Celeron Mobile 1.5GHz	Intel Core 2 Duo processor	Intel Atom D510
Chipset	Intel 91 x GME	Intel 945GME	ICH8M
HDD	SATA 2.5inch (Default 320GB)		
Memory	DDR2 SODIMM x 1 slot (Default 512MB up to 2GB)	DDR2 SODIMM x 2 slot (Default 1GB up to 4GB)	DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)
VGA	Intel 82915GM GMCH (Independent dual display)	Intel 82945GM GMCH (Independent dual display)	Intel Gen3.5+GFX Render Core
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution		
Internal I/O			
USB	3 Ports (reserved for Touch controller, SCR EMV card, Camera, MSR controller)		
PS/2	1 Keyboard with pin header		
RS-232	COM 4 reserved for CDP		COM 6 reserved for CDP
	COM 5 & 6 with 9pin header	COM 3 with 9pin header	COM 4 & 5 with 9pin header
D-SUB	Reserved for 2nd display		
Extension	Mini PCI		Mini PCIe
LVDS	Main display use		
External I/O			
Parallel	1 Port		
USB	Rear 2, Side 2		
PS/2	Mouse 1 / Keyboard 1		
RS-232	COM 1 ~ 3 with + 5/12V power output on 9pin	COM 1 ~ 2 with + 5/12V power output on 9pin	COM 1 ~ 3 with + 5/12V power output on 9pin
LAN	GbE LAN		
Audio	Line-out / Line-in / Mic		
Options			
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track		
SCR	EMV level		
Camera	Camera		-
Dallas	Dallas I-button reader		
Customer display	VFD type customer display (20 x 2)		
2nd LCD	12.1" LCD : 1024 x 768 resolution		
DVR	DVR Card : 4channels support		-
WiFi	Mini PCI for wireless LAN		
VGA	Mini PCI for VGA card		
Qualification	CE, FCC, KCC		CE, FCC, KCC, CCC
Power Supply	AC 110 or 220V (Max.240 watt)		INPUT : 100-240V~, 50/60Hz 1.5A OUTPUT : DC12V 5A
OS Support	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7		
Dimension(WxHxD)	385 x 395 x 265[mm]		

* 사양은 사전 통보없이 변경될 수 있습니다.

