

The one that creates a new trend

AnyShop II

New Sleek Style의 차별화된 디자인, 성능을 높인
프리미엄 POS SYSTEM!



15" LCD 터치스크린
정전용량식 터치스크린
LED Back-Light 탑재
Ultra-thin bezel



고객용 디스플레이
VFD 타입
2줄 20자



2nd LCD 디스플레이
15", 12.1", 10.1" 듀얼모니터
해상도 : 1024 x 768



다기능 일체형 장치
마그네틱 카드 리더
스마트 카드 리더



다양한 색상 힌지커버
다양한 색상의 커버 교체
(Option)



NEW TREND POS SYSTEM

- 정전용량식 터치스크린으로 더욱 정밀해진터치감
- LED Back Light 장착으로 더욱 선명해진 해상도
- Ultra-thin bezel 디자인으로 더욱 얇아지고 커진 화면
- 감각적인 Sleek Style + MODERN DESIGN

Convenient Use

- AMT 기술 채용으로 검색, OS복구 등의 원격 서비스 가능
- Smart Battery 적용으로 정전 시에도 데이터 손실 최소화

Easy Maintenance(Thumb-Screw)

- 드라이버 없이 손으로 탈착가능한 Thumb-Screw방식
- 옵션기기 탈부착 용이 / 손쉬운 유지보수

POS Software

POPS For Restaurant POS

외식솔루션



다양한 외식업종의 체계적 관리 통합외식 솔루션

- 판매, 결제, 재고, 사원관리 등 외식업종 통합관리
- 선불/후불/배달 통합서비스
- 회원관리, 단가관리, 쿠폰관리 등 다양한 업무 지원
- 사용자 이미지 및 디자인 변경(스킨 지원)

For Retail POS POPS

유통솔루션



대형마트, 편의점, 렌탈샵 등 전문화된 유통관리 솔루션

- 다매장 지원(통합재고관리, 수발주)
- 업종, 아이템별, 시리얼, 번들(Kit), BOX, 중량관리
- 프로모션, 쿠폰, 할인 등 다양한 판매정책 기능
- 사용자별 메뉴구성, 31가지 기본 스킨 제공

WEBPOS ASP솔루션



실시간 매장 운영상황 파악 효율적인 Web Solution

- 실시간 매출 및 재고분석 용이
- 본사와 가맹점 관리, 수발주 관리
- 최신 보안시스템을 이용한 정보 보안
- 쿠폰 및 SMS 전송 기능, Mobile ASP 제공

Specification

Models	AnyShop GM	AnyShop D5
CPU	Intel Core 2 Duo mobile CPU (T9400 CPU 6M Cache, 2.53 GHz)	Intel Atom processor D525 (1M Cache, 1.8 GHz, Dual Core for Pineview D)
Storage	SATA HDD 2.5inch (Default 320GB) SSD is available by option	SATA HDD 2.5inch(Default 320GB) SSD is available by option
Memory	DDR3-1066MHz SODIMM 2GB(MAX. 4GB)	DDR3-800MHz SODIMM 2GB(MAX. 4GB)
VGA	Integrated Intel Graphics Media Accelerator 4500MHD	Integrated Intel Gen3.5+GFX Render Core 400MHz(Pineview-D)
Display	<ul style="list-style-type: none"> • Resolution : 15" LED Backlight LCD 450 cd/m² or 15" TFT-LCD 300 cd/m²(1024 x 768 resolution) • Touch screen : True Flat Capacitive or 5-wired Resistive Touch 	<ul style="list-style-type: none"> • Resolution : 15" TFT-LCD 300 cd/m² • Touch screen : 5-wired Resistive Touch
AMT	Support AMT 4.0	-
Back up battery	Smart battery(supports up to 2 packs)	-
Internal I/O	<ul style="list-style-type: none"> • USB : 2 Ports(reserved for Touch controller, MSR controller) • RS-232 : COM 4 reserved for CDP, COM 6 reserved for MSR • VGA : Reserved for 2nd display • Extension : Mini PCIe • LVDS : 24bit LVDS • Parallel : 1 Port • PS/2 : 1 Port(Pin header reserved Keyboard & Mouse) 	<ul style="list-style-type: none"> • USB : 3 Ports(reserved for Touch controller, SCR EMV card, Camera, MSR controller) • RS-232 : COM 4 reserved for CDP, COM 5 & 6 with 9pin header • VGA : Reserved for 2nd display • Extension : Mini PCIe • LVDS : 24bit LVDS
External I/O	<ul style="list-style-type: none"> • USB : Rear 4, Side 4 • RS-232 : COM 1 ~ 3 with +5/12V power output on 9pin • LAN : Intel 82567LM Gigabit Ethernet • Speaker : 2 x 0.8W(Stereo) • Audio : Realtek ALC 892 / Line-out • Cash Drawer port : 1 port (COM5) 	<ul style="list-style-type: none"> • USB : Rear 2, Side 4 • PS/2 : Mouse 1 / Keyboard 1 • RS-232 : COM 1 ~ 3 with +5/12V power output on 9pin • LAN : Realtek RTL 8111E Ethernet • VGA : Reserved for 2nd display • Speaker : 2 x 0.8W(Stereo) • Audio : ALC 892 GR / Rear panel out(jack) : Line-out, Mic-in, Line-in
Options	<ul style="list-style-type: none"> • MSR : Comply with ISO 7811, Support 1 & 2 & 3 track • SCR : EMV level 1 • RS/232 : COM 5 (support 9pin header or DB9, shared with cash drawer port) • Dallas : Dallas I-button reader • VGA : D-SUB 15pin • Customer display : VFD type(20 x 2) • 2nd LCD : 10.1", 12.1", 15" LCD(1024 x 768 resolution) • 2nd storage : 2nd SSD Storage • Cash Drawer port : 1port • WiFi : Mini PCIe for wireless LAN 	<ul style="list-style-type: none"> • MSR : Comply with ISO 7811, Support 1 & 2 & 3 track • SCR : EMV level 1 • Dallas : Dallas I-button reader • Customer display : VFD type(20 x 2) • 2nd LCD : 10.1", 12.1", 15" LCD(1024 x 768 resolution) • 2nd storage : 2nd SSD Storage • Cash Drawer port : 1port • WiFi : Mini PCIe for wireless LAN
Qualification	CE, FCC, KC	CE, FCC, KC
Power	Adaptor 24V, 6A	Adaptor 12V, 5A
OS Support	Windows XP/XPE/7, WEPOS, POS Ready 2009/7	Windows XP/XPE/7, WEPOS, POS Ready 2009/7
Dimension(W x H x D)	415 x 305 x 385(mm)	415 x 305 x 385(mm)

* 사양은 사전 통보없이 변경될 수 있습니다.

POS 주변기기(Optional)



영수증프린터 A7

- Jam-free type
- 200mm/sec max
- 영수증프린터, 주방프린터



영수증프린터 A10M

- Jam-free type
- 220mm/sec max
- 영수증프린터, 주방프린터



고객표시창

- CDP
- 듀얼모니터(15", 12.1", 10.1" LCD)



유통키보드

- PS/2, USB type
- 98key



스캐너

- 72scans per second



금전함

- 4Bill / 8Coin