

The one that creates a new trend

# SlimPOS

공간절약형의 슬림하고 컴팩트한 디자인, 경제적인  
가격대의 고성능 POS System



**각도 조절이  
자유로운 터치스크린**  
상하 : 0 ~ 180°  
좌우 : 0 ~ 90°



**2nd LCD 디스플레이**  
12.1" 듀얼모니터  
해상도 : 1024 x 768



**고객용 디스플레이**  
VFD 타입  
2줄 20자



**다기능 일체형 장치**  
마그네틱 카드 리더  
스마트 카드 리더



**컴팩트한 디자인**  
설치장소에 구애 받지  
않는 슬림한 크기

# SlimPOS



- 사용자 시각에 맞도록 상하, 좌우 각도 조절이 자유로운 터치 스크린
- 전면부와 후면부에 다양한 포트 지원
- 공간 절약형의 슬림하고 컴팩트한 디자인
- 산업용 부품 사용으로 강한 내구성
- 설치 장소에 구애 받지 않는 크기
- 합리적이고 경쟁력 있는 가격
- 간편한 옵션기기 장착
- RoHS 인증

## System



	SlimPOS M	SlimPOS D5
CPU	Intel Celeron Mobile 1.5GHz	Intel Atom D510
Chipset	Intel 91 x GME	ICH8M
HDD	SATA 2.5inch (Default 160GB)	
Memory	DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)	DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)
VGA	Intel 82915GM GMCH (Independent dual display)	Intel Gen3.5 + GFX Render Core
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution	
<b>Internal I/O</b>		
USB	2 Ports (reserved for Touch controller & SCR EMV card)	
PS/2	1 Keyboard reserved for pin header	
RS-232	COM 4 reserved for VFD or 2nd display COM 5 & 6 with 9pin header	COM 4 reserved for VFD COM 5 & 6 with 9pin header
D-SUB	Reserved for 2nd display	
Extension	Mini PCI	Mini PCIe
LVDS	Main display use	
<b>External I/O</b>		
Parallel	1 Port	
USB	Front 2, Rear 2	
PS/2	Mouse 1 / Keyboard 1	
RS-232	COM 1 ~ 3 with + 5/12V power output on 9pin	COM 1 ~ 3 with + 5/12V power output on 9pin
LAN	GbE LAN	
Audio	Each 1 Line-out / Line-in / Mic	
<b>Options</b>		
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track	
SCR	EMV level	
Dallas	Dallas I-button reader	
Customer display	VFD type customer display (20 x 2)	
2nd LCD	12.1" LCD : 1024 x 768 resolution	
DVR	DVR Card : 4 channels support	-
WiFi	Mini PCI for wireless LAN	
VGA	Mini PCI for VGA card	
Qualification	CE, FCC, KCC	
Power Supply	AC 110 or 220V (Max.240 watt)	INPUT : 100-240V~, 50/60Hz 1.5A OUTPUT : DC12V 5A
OS Support	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7	



\* 사양은 사전 통보없이 변경될 수 있습니다.