



  
**POSBANK®**

The one that creates a new trend

NEW

# AnyShop eco

경제적인 가격, 강화된 성능의 Trend Item,  
AnyShop eco



## System



AnyShop eco	
CPU	Intel Atom processor D525 (1M Cache, 1.80 GHz)
Chipset	Intel ICH8M
HDD	SATA 2.5inch (Default 320GB)
Memory	DDR3-800 SODIMM x 1 slot (Default 1GB up to 4GB)
VGA	Intel Gen3.5+GFX Render Core 200MHz (Pineview-M)
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution
External I/O	
USB	Rear 2
PS/2	Mouse 1 / Keyboard 1
RS-232	COM 1 - 3 with +5/12V power output on 9pin
LAN	Realtek RTL 8111E Gigabit LAN
Audio	Realtek ALC888 Line-out / Line-in / Mic
Options	
MSR	Comply with ISO 7811, Support 1& 2 & 3 track
SCR	EMV level 1
Dallas	Dallas I-button reader
Customer display	VFD type (20 x 2)
2nd LCD	12.1" LCD : 1024 x 768 resolution
DVR	DVR Card : 4 channels support
WiFi	Mini PCI for wireless LAN
<b>Power Supply</b>	12V / 5A Adaptor
<b>OS Support</b>	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7
<b>Dimension</b>	419 x 406 x 262(mm)

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

## Contents

### POS terminal

- 03 AnyShop eco
- 04 mini O II
- 05 AnyShop
- 06 IMPREX
- 07 SlimPOS
- 08 BoxPOS

### Receipt printer

- 09 A7
- 10 A9+
- 11 A10+

### Peripheral

- 12 POSmo
- 13 PLU keyboard / Scanner / Cash drawer
- 14 'POPs' Restaurant solution
- 15 'Utong' Retail solution

NEW **mini O II**

10.1" 모니터의 경제적인 가격,  
감각적인 소형디자인 All In One Total  
POS System



### System



mini O II	
CPU	Intel Atom N270 1.6GHz processor
Chipset	Intel 945GSE+ICH7M
HDD	320GB HDD
Memory	DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)
VGA	Intel 945GSE GMA950 Engine
Printer	2" thermal printer (200mm/sec max, Auto cutter)
Display	10.1" (1024 x 768)
PCI	Mini PCIe
<b>External I/O</b>	
USB	Side 1, Rear 2
RS-232	COM 1 - 2 with + 5 / 12V power output on 9pin
LAN	GbE LAN
Cash drawer	1 x RJ11 , Cash drawer port
<b>Options</b>	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
SCR	IC card reader
Dallas	Dallas I-button reader
Keyboard	Mini standard keyboard or Programmable keyboard : 55 Key
Customer display	Rear or Pole type customer display (LCD, 16x2)
CF CARD	CF card reader
<b>Power Supply</b>	INPUT : 100-240V~, 50/60Hz 1.5A      OUTPUT : DC24V 2.5A
<b>OS Support</b>	Windows XP/XPE, POS Ready (WEPOS), Linux
<b>Dimension</b>	393 x 328 x 176 mm

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

# AnyShop

어느 매장과도 잘 어울리는 디자인,  
설계구조를 가진 Trend Item!



### System



	AnyShop M	AnyShop P	AnyShop D5
CPU	Intel Celeron Mobile 1.5GHz	Intel Core 2 Duo processor	Intel Atom D510
Chipset	Intel 91 x GME	Intel 945GME	ICH8M
HDD	SATA 2.5inch (Default 320GB)		
Memory	DDR2 SODIMM 512MB (up to 2GB)	DDR2 SODIMM x 2 slot (up to 4GB)	DDR2 SODIMM 1GB (up to 2GB)
VGA	Intel 82915GM GMCH	Intel 82945GM GMCH	Intel Gen3.5+GFX Render Core
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution		
<b>External I/O</b>			
Parallel	1 Port		
USB	Rear 2, Side 2		
PS/2	Mouse 1 / Keyboard 1		
RS-232	COM 1 - 3 with + 5/12V power output on 9pin	COM 1 - 2 with + 5/12V power output on 9pin	COM 1 - 3 with + 5/12V power output on 9pin
LAN	GbE LAN		
Audio	Line-out / Line-in / Mic		
<b>Options</b>			
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track		
SCR	EMV level		
Camera	Camera		-
Dallas	Dallas I-button reader		
Customer display	VFD type customer display (20 x 2)		
2nd LCD	12.1" LCD : 1024 x 768 resolution		
DVR	DVR Card : 4channels support		-
WiFi / VGA	Mini PCI		Mini PCIe
<b>Power Supply</b>	AC 110 or 220V (Max. 240 watt)		INPUT : 110-240V~, 50/60Hz 1.5A OUTPUT : DC12V 5A
<b>OS Support</b>	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7		
<b>Dimension</b>	385 x 395 x 265 mm		

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

# IMPREX

세련된 디자인, 안정성을 겸비한  
All In One POS System



## System



	IMPREX M	IMPREX P	IMPREX D5
CPU	Intel Celeron Mobile 1.5GHz	Intel Core 2 Duo processor	Intel Atom D525
Chipset	Intel 91xGME	Intel 945GME	Intel ICH8M
HDD	SATA 2.5inch (max 2, Default 320GB)		
Memory	DDR2 SODIMM 512MB (up to 2GB)	DDR2 SODIMM x 2 slot (up to 4GB)	DDR3 SODIMM x 1 slot (up to 2GB)
VGA	Intel 82915GM GMCH	Intel 82945GM GMCH	Intel Gen3.5 + GFX Render Core
Printer	3" thermal printer (220mm/sec max, Auto cutter)		
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution		
<b>External I/O</b>			
USB	Rear 2, Side 3		
PS/2	Mouse 1 / Keyboard 1		
RS-232	COM 1 - 3 with + 5/12V power output on 9pin	COM 1 - 2 with + 5/12V power output on 9pin	COM 1 - 3 with + 5/12V power output on 9pin
LAN	GbE LAN		
Audio	Line-out / Line-in / Mic		
C.D	Cash drawer port		
<b>Options</b>			
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track		
SCR	EMV level		
Dallas	Dallas I-button reader		
Customer display	VFD type customer display (20 x 2)		
2nd LCD	12.1" LCD : 1024 x 768 resolution		
2nd HDD	2nd HDD storage		
DVR	DVR Card : 4 channels support		
WiFi / VGA	Mini PCI		
Power Supply	AC 110 - 220V (Max.240 watt) Free voltage	INPUT : 100-240V-, 50/60Hz 1.5A OUTPUT : DC24V 6A	
OS Support	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7		
Dimension	405 x 351 x 345 mm		

\* 사양은 사진 톨보 없이 변경 될 수 있습니다.

# SlimPOS

공간절약형의 슬림하고 컴팩트한 디자인,  
경제적인 가격대의 고성능  
POS System



## System



SlimPOS D5	
CPU	Intel Atom D510
Chipset	ICH8M
HDD	SATA 2.5inch (Default 320GB)
Memory	DDR2 SODIMM x1GB (up to 2GB)
VGA	Intel Gen3.5 + GFX Render Core
Display	15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution
<b>External I/O</b>	
Parallel	1 Port
USB	Front 2, Rear 2
PS/2	Mouse 1 / Keyboard 1
RS-232	COM 1 - 3 with + 5/12V power output on 9pin
LAN	GbE LAN
Audio	Line-out / Line-in / Mic
<b>Options</b>	
MSR	Comply with ISO 7811, Support 1 & 2 & 3 track
SCR	EMV level
Dallas	Dallas I-button reader
Customer display	VFD type customer display (20 x 2)
2nd LCD	12.1" LCD : 1024 x 768 resolution
DVR	-
WiFi / VGA	Mini PCI
Power Supply	INPUT : 110-240V-, 50/60Hz 1.5A OUTPUT : DC12V 5A
OS Support	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7
Dimension	400 x 360 x 355 mm

\* 사양은 사진 톨보 없이 변경 될 수 있습니다.

# BoxPOS

LCD 모니터를 장착하여 사용하는 공간 절약형의  
고성능 POS System



# NEW A7 Receipt Printer

컴팩트한 디자인, 경제적인 가격의  
Jam-free 미니프린터



## System



	BoxPOS N2	BoxPOS P
CPU	Intel Atom N270 1.6GHz processor	Intel Core 2 Duo processor
Chipset	Intel 945GSE + ICH7M	Intel 945GME
HDD	SATA 2.5inch [Default 320GB]	
Memory	DDR2 SODIMM 1GB (up to 2GB)	DDR2 SODIMM x 2 slot (up to 4GB)
VGA	Intel 945GSE GMA950 Engine	Intel 82945GM GMCH
PCI	Mini PCIe	Mini PCI
<b>External I/O</b>		
Parallel	1Ports	
USB	Front 2, Rear 2	
PS/2	Keyboard 1	
RS-232	COM 1, COM 2, COM 3, COM 4	COM 1 - 2 with + 5 / 12V power output on 9pin
Cash drawer	1 x RJ11 , Cash drawer port (option)	
LAN	Realtek RTL8111D Gigabit LAN	
Power Supply	INPUT : 110-240V-, 50/60Hz 1.5A OUTPUT : DC12V 5A	AC 110 or 220V [Max. 240watt]
OS Support	Windows CE 6.0 on SSD, Windows XP/ XPE, POS Ready (WEPOS) on HDD, Linux	Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7
Dimension	280 x 78 x 355 mm	

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

## System



A7	
Printing Method	3" Jam-free direct thermal
Printing Speed	170 mm/sec max
Dot Density (DPI)	203.2
Dot Pitch (mm)	0.125*0.125
Effective Printing Width	72mm, 576dots
Printing Direction	Unidirectional with friction feed
Character/Line	Font A (12*24) 42 columns Font B (10*20) 56 columns
Paper	Type Thermal paper Width 79.5mm (±0.5mm) Thickness 0.07mm Roll diameter 83 Ømm
Reliability	TPH Life 100km MCBF 60,000,000 lines
Character/Set	Alphanumeric character 95 Extended graphic 128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR
Emulation	ESC/POS command compatible
Driver	Windows / OPOS
Interface	Serial / USB / Ethernet / Wi-fi
Power	DC 24V, 2.5A
Data Buffer	4 Kbyte
Cutting	Life 700,000 cuts Cutting method Partial Cut & Full Cut
Temperature	Operation 0 ~ 40°C Storage -20 ~ 60°C
Dimension	136 x 162.5 x 122 mm

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

# A9+ Receipt Printer

빠른 속도와 강력한 성능의 새로운 미니프린터



## System



A9+		
Printing Method	3" direct thermal	
Printing Speed	220 mm/sec max	
Dot Density (DPI)	203.2	
Dot Pitch (mm)	0.125*0.125	
Effective Printing Width	74mm, 588dots	
Printing Direction	Unidirectional with friction feed	
Character/Line	Font A	[14*28] 42 columns
	Font B	[10*20] 56 columns
Paper	Type	Thermal paper
	Width	79.5mm (±0.5mm)
	Thickness	0.07mm
	Roll diameter	83 Ømm
Reliability	TPH Life	100km
	MCBF	60,000,000 lines
Character/Set	Alphanumeric character	95
	Extended graphic	128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR	
Emulation	ESC/POS command compatible	
Driver	Windows / OPOS	
Interface	Serial / Parallel / USB / Ethernet / USB+Serial combo / Wi-fi / Bluetooth	
Power	DC 24V, 2.5A	
Data Buffer	4 Kbyte	
Cutting	Life	1,000,000 cuts
	Cutting method	Partial Cut
Temperature	Operation	0 ~ 40°C
	Storage	-20 ~ 60°C
Dimension	145 x 215 x 130 mm	

\* 사양은 사전 통보 없이 변경 될 수 있습니다.

# A10+ Receipt Printer

고성능의 빠르고 안정된 고급디자인의 미니프린터



## System



A10+		
Printing Method	3" direct thermal	
Printing Speed	220 mm/sec max	
Dot Density (DPI)	203.2	
Dot Pitch (mm)	0.125*0.125	
Effective Printing Width	74mm, 588dots	
Printing Direction	Unidirectional with friction feed	
Character/Line	Font A	[14*28] 42 columns
	Font B	[10*20] 56 columns
Paper	Type	Thermal paper
	Width	79.5mm (±0.5mm)
	Thickness	0.07mm
	Roll diameter	83 Ømm
Reliability	TPH Life	100km
	MCBF	60,000,000 lines
Character/Set	Alphanumeric character	95
	Extended graphic	128 x 35 page
Barcode	EAN-8, EAN-13, CODE39, CODE93, CODE128, ITF, UPC-A, UPC-E, CODABAR	
Emulation	ESC / POS command compatible	
Driver	Windows / OPOS	
Interface	Serial / Parallel / USB / Ethernet / USB+Serial combo / Wi-fi / Bluetooth	
Power	DC 24V, 2.5A	
Data Buffer	4 Kbyte	
Cutting	Life	1,000,000 cuts
	Cutting method	Partial Cut
Temperature	Operation	0 ~ 40°C
	Storage	-20 ~ 60°C
Dimension	142 x 201 x 126 mm	

\* 사양은 사전 통보 없이 변경 될 수 있습니다.

# POSmo

슬림한 디자인, 사용자 시각에 맞도록 각도 조절이 가능한 스탠드형 15" LCD 터치모니터



## System



### POSmo

Display Type	TFT LCD 15"
Touch Screen	5-wired resistive type
Display Size	15"
Colors	16 million
Resolution	1024 x 768
Contrast Ratio	600:1
Brightness	LCD panel : 250cd/m <sup>2</sup>
Response Time	8mm/sec
Viewing Angle	160°
Input Connector	RGB signal 1 Port, 12V Keyboard input port for MSR option
Output Connector	USB Touch Controller 1 Port, Keyboard output port for MSR option
Option	Comply with ISO 7811, Support 1 & 2, 2 & 3, 1 & 2 & 3 track
Power	12VDC / 3A

\* 사양은 사진 정보 없이 변경 될 수 있습니다.

# PLU keyboard

- 키별 메뉴, 상품, 업무 기능 등록 가능
  - 카드리더기 일체형 제품
- 인터페이스 방식 : PS/2, USB
  - programmable 키수 : 98개



# Scanner



# Cash drawer



# POPs

For Restaurant POS

다양한 외식 업종의 체계적인 관리를 제공하는  
통합 외식 Solution

- 간편한 인증 Process 도입
- 업데이트된 편리하고 다양한 기능
- 통합 서비스 형태 지원 (선불, 후불, 배달)
- 사원별, 업무 단위별 체계적인 보안지원
  - 사용자 이미지 및 디자인 변경
  - 특정지점의 백업데이터 복원
- 매장 실시간 상태, 속보, 경영정보 지원
  - 화상키보드 지원
- 단가관리, 재고관리, 쿠폰관리 등 체계적인 관리 지원
- 사원 근태/급여 기능, 비주열 기능 강화



LOGIN



Main 화면




# Utong

Retail Point of Sales

'Utong' 솔루션은 도소매점, 대형 할인마트, 문구 등  
유통업종의 매장관리, 입출고관리, 재고관리 등  
다양한 통합관리 Solution

- 다양한 스킨 지원 (31가지 기본 스킨 제공)
- 사용자 정의 리포트 검색 (분류, 품목, 시간, 월, 일간 매출 조회)
  - 프로모션 기능 지원
- 외국환 결제 및 다양한 복합 결제 가능
  - 사용자별 메뉴 구성
  - 사원별 언어 선택 가능
  - 사용자 정의 영수증 출력
  - 체계적인 보안지원
- 다매장 지원 (통합 재고 관리, 수발주 기능)



LOGIN



POS 판매화면



POS 주문화면



테이블관리



POS 결제



Backoffice - Login



 [www.posbank.co.kr](http://www.posbank.co.kr)

**POSBANK<sup>®</sup>**

서울 금천구 가산동 429-1 뉴티캐슬 805~808호  
대표전화. 1588-6335 서비스센터. 1588-6312